

# **Specification Sheet**

## **Como Collection**











2118 Lora

2112 Autonno





2021 Cenere

## **PRODUCT DETAILS**

Product Type Rigid Engineered Luxury Vinyl

Collection **Como Collection** Construction Solid Vinyl Plank

Classification ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed

Overall Thickness 5.5mm (0.2165") Wear Layer 22mil (0.55mm) Underlayment 1.5mm IXPE (0.0591")

Micro Bevel Edge Profile Surface Finish Ceramic Bead

Embossing **Photo Match Embossing** 

Edge Profile Easy-to-install with I4F Locking system

7" W x 48" L (180x1220mm) Size

18.91 SQFT/CTN Square Feet Per Carton Pieces Per Carton 8 PIECES/CTN

Weight Per Carton 14.93 KGS/CTN 32.91 LBS/CTN

Carton Per Pallet 65 CTNS/PLT Floating/Glue Down Installation Method

#### **TECHNICAL PROPERTY**

Dimensional Stability AŞTM F2199 - Passes - ≤0.2% / lineal ft. (305 mm)

Curling ISO 23999 - Passes - ≤2mm

Static Load ASTM F970 - Passes - ≤0.005" (0.13mm) (without underlayer)

Static Load Limit SIM Test - 1000 psi (0.02mm) (without underlayer)

Residual Indentation ASTM F1914 - Passes - Average: ≤0.007" (0.18mm) (without underlayer) Resistance to Chemicals

ASTM F925-Passes-No more than a slight change in surface

Resistance to Heat ASTM F1514 - Passes - Average ΔE < 8.0 Resistance to Light ASTM F1515 - Passes - Average  $\Delta E < 8.0$ Critical Radiant Flux ASTM E648 - Passes - Class I: ≥ 0.45 W/Sq.cm

VOCs/TVOCs, Formaldehyde CDPH/EHLB Method v1.2 Compliant

Substances of Very High Concern REACH SVHC 191 - Passes - Per Substance: ≤0.1% w/w

Heavy Metals ASTM F963 - Passes

Phthalates ASTM D7823 - Passes - CPSC-CH-C1001-09.3

Slip Resistance ASTM D2047- Dry: 0.38 Wet: 0.90

Fungi Resistance ASTM G21-15 - Passes

**IIC Rating** ASTM E492 & ASTM E989 - Result: 70 STC Rating **ASTM E90 & ASTM E413 - Result: 67** 

## **SUSTAINBILITY**

Smoke Density

Material Virgin Vinyl

Certification Floor Score® certified **Environmental Product Declaration EPD Vinyl Click** 

Health Product Declaration HPD 2.1 Vinyl Click - 1000 ppm

## **SERVICE**

Warranties **Limited Lifetime Warranty** 











ASTM E662 - Passes - Flaming & Non Flaming≤ 450

