

Canton Collection



PRODUCT DETAILS

Product Type	Glue Down LVT
Collection	Canton
Construction	Vinyl Dryback Plank
Classification	ASTM F1700-Class III, Type A-Smooth, Type B-Embossed
Overall Thickness	2.0 mm (.08")
Wear Layer	6 mil (0.15 mm)
Edge Profile	Square
Surface Finish	UV Coating
Embossing	Photo Match Embossing
Size	7" W x 48" L / 177.8 mm x 1219.2 mm
Square Feet Per Carton	37.33 sf/ctn
Pieces Per Carton	16 pieces/ctn
Weight Per Carton	12 kg/ctn (26.46 lbs/ctn)
Carton Per Pallet	70 ctns/plt
Installation Method	Glue Down



5001
Arbor



5002
Barnett

TECHNICAL PROPERTY

Dimensional Stability	ASTM F2199 -Passes- ≤ 0.02 " / lineal ft. (305 mm)
Curling	ISO 23999 - Passes - ≤ 2 mm
Static Load	ASTM F970 -Passes- ≤ 0.005 " (0.13mm)
Flexibility	ASTM F137 -Passes- 1" mandrel passed
Residual Indentation	ASTM F1914 -Passes- Avg $\leq 8\%$, Max 10%
Resistance to Chemicals	ASTM F925 -Passes- No more than "Slight Change"
Resistance to Heat	ASTM F1514 -Passes- Average $\Delta E < 8.0$
Resistance to Light	ASTM F1515 -Passes- Average $\Delta E < 8.0$
Critical Radiant Flux	ASTM E648 -Passes- Class I: ≥ 0.45 W/Sq.cm
VOCs/TVOCs	CDPH/EHLB -Compliant
Substances of Very High Concern	REACH SVHC 191 -Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 -Passes
Phthalates	ASTM D7823 /CPSC-CH-C1001-09.3 -Passes
Slip Resistance	DIN51130 - Result: Class R10
Fungi Resistance	ASTM G21 - Passes

SUSTAINABILITY

Material	Clean Recycle W/O DOTP
Certification	FloorScore® certified
Environmental Product Declaration	EPD Vinyl Flooring

SERVICE

Warranties	Limited Lifetime Warranty
------------	---------------------------

