


**COMO**

STONE POLYMER COMPOSITE

**TECHNICAL DATA SHEET**



*Bella Flooring*  
**GROUP**



# COMO

# STONE POLYMER COMPOSITE

# TECHNICAL DATA SHEET

## Bella Flooring GROUP

### PRODUCT DETAILS

Product Type	Rigid Engineered Luxury Vinyl
Collection	Como
Construction	Stone Polymer Composite
Classification	ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed
Overall Thickness	5.5mm (0.2165")
Wear Layer	22mil (0.55mm)
Underlayment	1.5mm IXPE (0.0591")
Edge Profile	Micro Bevel
Surface Finish	UV/Ceramic Bead + BellaSure
Embossing	Photo Match Embossing
Edge Profile	Easy-to-install with I4F Drop Lock Technology
Size	7" W x 48" L (180x1220mm)
SQ. Feet Per Carton	23.90 SQFT/CTN
Pieces Per Carton	10 PIECES/CTN
Weight Per Carton	41 LBS/CTN
Carton Per Pallet	55 CTNS/PLT
Installation Method	Floating / Glue Down



### TECHNICAL PROPERTIES



<b>Dimensional Stability</b>	ASTM F2199   Passes   $\leq 0.2\%$ / lineal ft. (305 mm)
<b>Curling</b>	ISO 23999   Passes   $\leq 2\text{mm}$
<b>Static Load</b>	ASTM F970   Passes   $\leq 0.005\text{"}$ (0.13mm) (without underlayer)
<b>Static Load Limit</b>	SIM Test   Passes   1000 psi (0.02mm) (without underlayer)
<b>Residual Indentation</b>	ASTM F1914   Passes   Average: $\geq 0.007\text{"}$ (0.18mm) (without underlayer)
<b>Resistance to Chemicals</b>	ASTM F925   Passes   No more than a slight change in surface
<b>Resistance to Heat</b>	ASTM F1514   Passes   Average $\Delta E < 8.0$
<b>Resistance to Light</b>	ASTM F1515   Passes   Average $\Delta E < 8.0$
<b>Critical Radiant Flux</b>	ASTM E648   Passes   Class I: $\geq 0.45 \text{ W/Sq.cm}$
<b>Smoke Density</b>	ASTM E662   Passes   Flaming & Non Flaming $\leq 450$
<b>VOCs/TVOCs, Formaldehyde</b>	CDPH/EHLB Method v1.2   Compliant   V1.2-2017
<b>Substances of Very High Concern</b>	REACH SVHC 191   Passes   Per Substance: $\leq 0.1\%$ w/w
<b>Heavy Metals</b>	ASTM F963   Passes
<b>Phthalates</b>	ASTM D7823   Passes   CPSC-CH-C1001-9.3
<b>Slip Resistance</b>	ASTM D2047   Passes   Dry: 0.38 Wet: 0.90
<b>Fungi Resistance</b>	ASTM G21-15   Passes
<b>IIC Rating</b>	ASTM E492 & ASTM E989   Result: 70
<b>STC Rating</b>	ASTM E90 & ASTM E413   Result: 67

### SUSTAINABILITY & WARRANTIES



Material Certification	Virgin Vinyl
Environmental Product Declaration	Floor Score® Certified
Health Product Declaration	EPD Vinyl Click
	HPD 2.1 Vinyl Click - 1000 ppm
Warranties	Lifetime Residential & 20-Year Commercial





100% WATERPROOF

COMO

EASY INSTALL

STONE POLYMER COMPOSITE LUXURY FLOORING



LORA



SIX UNIQUE COLORS AVAILABLE



LUNA AVORIO



FALCO



BRUNO NOCE



AUTONNO



LORA



CENERE

DIMENSIONS	7" X 48"
TOTAL THICKNESS	5.5 MM
WEAR LAYER	22 MIL / .55 MM
EDGE PROFILE	MICROBEVEL
ATTACHED PAD	1.5 MM IXPE
SQUARE FEET PER CARTON	23.90
CARTONS PER PALLET	55
SQUARE FEET PER PALLET	1,314.50
LOCKING SYSTEM	I4F DROP LOCK

CORRESPONDING TRANSITIONS

Add a touch of finished perfection to every installation with exact color matched transitions.




END CAP



T-MOULDING



REDUCER



FLUSH STAIR NOSE

NEED ADDITIONAL DETAILS?

Scan this QR code with your smart device's camera to visit this product's page on our website.

